

# OTHERS DOOR FITTING

อุปกรณ์อื่น ๆ สำหรับประตู



## AF - 435

อุปกรณ์กันเสียงและฝุ่น สำหรับประตู  
→ 13 x 30 mm | ↓ 22 mm | ← 48 dB



### Main features

- Seal height up to ↓ 22 mm
- Acoustic insulation up to ← 48 dB in case of an optimal sealing
- Protected silicone lips since deeper embedded
- Door can be adapted on bottom without removal
- Unilateral and soundless release, silent seal
- Due to parallel drop-down no trailing on the floor
- Automatic compensation at inclined floors
- One groove width for Planet HS and RH (uneven floors)
- For double leaf folding doors with flush bolt or driving bar
- High-grade silicone lip, simple lift height adjustment
- Can be shortened up to the next shorter length on stock
- No extra need to cut off silicone at both ends
- 7 years warranty

### Versions / options

- Planet HS → RD ← 48 dB, smoke-shielding
- Planet HS → FH+RD ← 48 dB, fire-retardant + smoke-shielding
- Option sliding door ← 48 dB
- Silicone lip extended by 8 mm
- Anti-bacterial silicone lip is optional
- Possibility of silicone-free (TPE) execution
- Option Double-shortening → refer to chapter Accessories | TR125
- Special versions on request

### Door types with Planet HS



Double leaf doors → refer to chapter Accessories | Flush bolt, drilling

### More functions



### Technical specifications

Profile material	aluminum, → 13 x 30 mm
Groove size	width 13,1 mm with depth 30,5 up to 40 mm
Seal profile	high-grade silicone or high-grade self-extinguishing silicone
Seal height	up to ↓ 22 mm
Sound absorption value	up to ← 48 dB at 7 mm space to the floor; up to ← 42 dB at 18 mm space to the floor
Lift height adjustment	on the release knob with an Allen key 3 mm
Lengths in stock	335, 460, 585, 710, 835, 960, 1085, 1210, 1335, 1460 mm
Special lengths	on request up to 6000 mm for wing- and sliding doors
Release	unilaterally on hinge side
Can be shortened	up to the maximum of 125 mm (335 mm only 115 mm)
Fastening	on the side with stainless steel angle brackets and screws
Frame protector plate	stainless, hammer fixed, 20 x 20 mm
Test approvals	on request

