

HINGE SYSTEM

บานพับ



POCKET DOOR SYSTEM

Exedra2 Smart

The evolution of the Exedra system, which enables the simultaneous movement of two linked doors. Exedra2 Smart is the version that requires less depth of the cabinet; the door edges are visible when they are folded into the cabinet.

- ✓ MAXIMUM WEIGHT FOR SINGLE DOOR: 25 KG
- ✓ DOORS THICKNESS: MIN 18 MM - MAX 25 MM
- ✓ WIDTH OF SINGLE DOOR: MIN 550 MM - MAX 850 MM
- ✓ DOORS HEIGHT: MIN 1800 MM - MAX 2600 MM

Exedra2 Smart Technical Information

DOUBLE pocket door system with cam-assisted door extraction and cushioned door insertion.

Door characteristics:

Adjustment:

- vertical adjustment ± 5 mm
- horizontal adjustment ± 3.5 mm
- front adjustment: - upper ± 3 mm
- lower ± 2 mm
- Maximum weight for single door: 25 Kg
- Doors thickness: min 18 mm - max 25 mm
- Width of single door -
Exedra2 Smart: min 550 mm - max 850 mm
- Doors height: min 1800 mm - max 2600 mm

1. Unique patented door opening system. The external surfaces of the doors are always protected during the opening and closing system.
2. Non- loadbearing track on the top of the cabinet.
3. Magnetic buffer for assisted cushioned doors insertion.
4. Structural aluminum frame for doors movement.
5. Frontal insertion of the loadbearing frame facilitating its installation in a wall recess.
6. Side frame to support the lower loadbearing track. All of one lead is covered by the side panel. The track does not require ground support.
7. Antirush device.

Exedra2 Smart

